

BALL VALVES

0657EN 02/2021

VALVE FOR WATER FOR HEATING/COOLING SYSTEMS
NOT DANGEROUS GAS AND LIQUID HYDROCARBONS
STANDARD PORT - R258CC SERIES



R258CC

Description

Ball valve, with compression connections for copper pipes.
Standard port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color
R258CX002	Ø 15 x Ø 15	Chrome plated brass	Lever	Red
R258CX005	Ø 22 x Ø 22	Chrome plated brass	Lever	Red
R258CX006	Ø 28 x Ø 28	Chrome plated brass	Lever	Red

Technical data

Main features and materials

- Suitable for water for heating/cooling systems, not dangerous gas and liquid hydrocarbons*
- Standard port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Steel lever handle with anti-corrosion treatment and red PVC coating


Field of applications

- Min. working temperature: -20 °C with 50 % glycol solutions
- Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar)
- Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for Ø 15, Ø 22
3,5 MPa (35 bar) for Ø 28
- Temperature range with liquid hydrocarbons*: -20÷60 °C
- Max. working pressure at 20 °C with liquid hydrocarbons*: 1,2 MPa (12 bar)

* Please consult Giacomini technical support, to check the compatibility of the product with the specific hydrocarbon.

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R258CX002	14	72	32	49	15	77	ch.24	10,2
R258CX005	18	88	40	64	18	94	ch.32	18,5
R258CX006	22	97	45	73	23	94	ch.39	36,3



Product specifications

R258CC

Ball valve, with compression connections for copper pipes. Suitable for water for heating/cooling systems, not dangerous gas and liquid hydrocarbons. Valve made of UNI EN 12165 CW617N chrome plated brass. Standard port. Steel lever handle with anti-corrosion treatment and red PVC coating. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Min. working temperature: -20 °C with 50 % glycol solutions. Max. working temperature with dry saturated steam: 185 °C with 1,05 MPa (10,5 bar). Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for Ø 15, Ø 22; 3,5 MPa (35 bar) for Ø 28. Temperature range with liquid hydrocarbons: -20÷60 °C. Max. working pressure at 20 °C with liquid hydrocarbons: 1,2 MPa (12 bar).

Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy