

BALL VALVES

0904EN March 2020

VALVE FOR WATER FOR HEATING/COOLING SYSTEMS
AND NOT DANGEROUS GAS
FULL PORT - R780P-1 SERIES



GIACOMINI
WATER E-MOTION



R780P-1

Description

Angle ball valve, with male-female threaded connections with nut and gasket, specific for under boiler use and for meters connection.
Full port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color	Notes
R780PX013	G 1/2"M x Nut G 1/2"F	Nickel plated brass	T-handle, one lug	Red	Under boiler use, for meter connection
R780PX014	G 3/4"M x Nut G 3/4"F	Nickel plated brass	T-handle, one lug	Red	Under boiler use, for meter connection

Technical data

Main features and materials


- Suitable for water for heating/cooling systems and not dangerous gas
- Full port
- Valve made of UNI EN 12165 CW617N nickel plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium one lug T-handle, red painted

Field of applications

- Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions)
- Max. working pressure at 20 °C with water and not dangerous gas: 1,6 MPa (16 bar)

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	H' [mm]	Kv
R780PX013	15	65	17	78	40	44	wr.26	wr.24	4,8
R780PX014	20	75	21	86	43	52	wr.32	wr.30	8,0



Product specifications

R780P-1

Angle ball valve, with male-female threaded connections with nut and gasket, specific for under boiler use and for meters connection. Suitable for water for heating/cooling systems and not dangerous gas. Valve made of UNI EN 12165 CW617N nickel plated brass. Full port. Aluminium one lug T-handle, red painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions). Max. working pressure at 20 °C with water and not dangerous gas: 1,6 MPa (16 bar).

Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ consulenza.prodotto@giacomini.com

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy