


**R251WST**

### Description

Ball valve, with female-female connections, with drain cock with hose connection  $\varnothing$  9 mm, for pipes with high insulation thickness, specific for domestic water.  
Standard port.

### Versions and product codes

Product code	Connections	Drain cock size	Finishing	Handle type	Handle color	Notes
R251SX103	Rp 1/2" x Rp 1/2"	1/4"	Chrome plated brass	Extended T-handle	Green, red, blue plates	With drain cock, for pipes with high insulation thickness
R251SX104	Rp 3/4" x Rp 3/4"	1/4"	Chrome plated brass	Extended T-handle	Green, red, blue plates	With drain cock, for pipes with high insulation thickness
R251SX105	Rp 1" x Rp 1"	1/4"	Chrome plated brass	Extended T-handle	Green, red, blue plates	With drain cock, for pipes with high insulation thickness
R251SX106	Rp 1-1/4" x Rp 1-1/4"	3/8"	Chrome plated brass	Extended T-handle	Green, red, blue plates	With drain cock, for pipes with high insulation thickness

**I** The chrome plated version is last in production, the product will be replaced by the nickel plated version.

### Technical data

#### Main features and materials


- Specific for domestic water
- Standard port
- Valve made of UNI EN 12165 CW617N chrome plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Extended plastic T-handle, with green, red and blue plates
- Drain cock with hose connection  $\varnothing$  9 mm

#### Field of applications

- Temperature range: 5÷110 °C, possibility of 120 °C for short periods of time
- Max. working pressure at 20 °C with water and not dangerous gas:  
4,2 MPa (42 bar) for 1/2", 3/4"  
3,5 MPa (35 bar) for 1", 1-1/4"

### Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R251SX103	14	60	32	77	15	78	wr.25	10,2
R251SX104	18	71	36	86	18	78	wr.32	18,5
R251SX105	22	83	43	95	23	78	wr.40	36,3
R251SX106	28	102	56	104	28	78	wr.49	73,5



### Product specifications

#### R251WST

Ball valve, with female-female connections, with drain cock with hose connection  $\varnothing$  9 mm, for pipes with high insulation thickness. Specific for domestic water. Valve made of UNI EN 12165 CW617N chrome plated brass. Standard port. Extended plastic T-handle, with green, red and blue plates. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: 5÷110 °C, possibility of 120 °C for short periods of time. Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for 1/2", 3/4"; 3,5 MPa (35 bar) for 1", 1-1/4".

#### Additional information

For more information, go to [www.giacomini.com](http://www.giacomini.com) or contact our technical assistance service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ [consulenza.prodotti@giacomini.com](mailto:consulenza.prodotti@giacomini.com)

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy