



**R705K**



**R706K**

**Description**

Radiator system kit composed by valve with manual handwheel and lockshield, with male threaded for iron pipe connections.

**Technical data**

- Temperature range: 5÷110 °C
- Max. working pressure: 16 bar

**Versions and product codes**


Product code	Size	Type	Packaging
R705KX003	1/2"	Angle version	Standard
R706KX003	1/2"	Straight version	
R705KX033	1/2"	Angle version	Bulk

**Materials**


- Valve and lockshield bodies: EN 12165 - CW617N chrome plated brass
- Valve handwheel: ABS

**Loss of pressure**

**R705K**





**R706K**




**Dimensions**


**R705K**

Valve							
							
G x B	I [mm]	H [mm]	J [mm]	L [mm]	M [mm]	K [mm]	W [mm]
1/2"M x 1/2"F	50	63	21	69	37	26	30

Lockshield							
							
G x B	I [mm]	H [mm]	J [mm]	L [mm]	K [mm]	Y [mm]	W [mm]
1/2"M x 1/2"F	53	41	21	67	25	22	30

**R706K**

Valve							
							
G x B	I [mm]	H [mm]	J [mm]	L [mm]	M [mm]	K [mm]	W [mm]
1/2"M x 1/2"F	50	66	17	74	37	25	30

Lockshield							
							
G x B	I [mm]	H [mm]	J [mm]	L [mm]	Y [mm]	K [mm]	W [mm]
1/2"M x 1/2"F	51	45	17	74	22	25	30

**Additional information**

For additional information please check the website [www.giacomini.com](http://www.giacomini.com) or contact the technical service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ [consulenza.prodotti@giacomini.com](mailto:consulenza.prodotti@giacomini.com)  
 This pamphlet is merely for information purposes. Giacomini S.p.A. retains the right to make modifications for technical or commercial reasons, without prior notice, to the items described in this pamphlet. The information described in this technical pamphlet does not exempt the user from following carefully the existing regulations and norms on good workmanship.  
 Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy