

BALL VALVES

0641EN March 2020

VALVE SPECIFIC FOR DOMESTIC WATER
FULL PORT - R854VWL SERIES

GIACOMINI
WATER E-MOTION



R854VWL

Description

Ball valve, with female threaded-press connections (for copper pipe complying with EN 1057; for stainless steel pipe complying with EN 10217-7 and EN 10312; for carbon steel pipe complying with EN 10305-3), specific for domestic water.

Full port.

Versions and product codes

Product code	Connections	Tongs profile	Finishing	Handle type	Handle color
R854VY137	Rp 1 1/2" x Ø 42	V	Brass	Large lever	Green
R854VY138	Rp 2" x Ø 54	V	Brass	Large lever	Green

Technical data

Main features and materials

- Specific for domestic water
- Full port
- Valve made of UNI EN 12165 CW617N brass
- Stem with double O-Ring
- Double O-Ring (black) on the press fittings, complies with EN 681-1 standards
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Steel lever handle with anti-corrosion treatment and green PVC coating
- Pressable with "V" profile tongs




V

Field of applications

- Temperature range: 5÷110 °C
- Max. working pressure at 20 °C with water and not dangerous gas: 2,8 MPa (28 bar)

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R854VY137	40	131	79	107	37	137	wr.55	140
R854VY138	50	154	91	122	44	137	wr.69	211



Product specifications

R854VWL

Ball valve, with female threaded-press connections (for copper pipe complying with EN 1057; for stainless steel pipe complying with EN 10217-7 and EN 10312; for carbon steel pipe complying with EN 10305-3), specific for domestic water. Valve made of UNI EN 12165 CW617N brass. Full port. Steel lever handle with anti-corrosion treatment and green PVC coating. Stem with double O-Ring. Double O-Ring (black) on the press fittings, complies with EN 681-1 standards. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: 5÷110 °C. Max. working pressure at 20 °C with water and not dangerous gas: 2,8 MPa (28 bar).

Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📞 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy