

BALL VALVES

0618EN March 2020

VALVE SPECIFIC FOR DOMESTIC WATER
FULL PORT - R951W SERIES



GIACOMINI
WATER E-MOTION



Description

DADO ball valve, with female-female connections, heavy series, specific for domestic water.

Full port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color	Notes
R951WX002	Rp 3/8" x Rp 3/8"	Nickel plated brass	T-handle	Green	DADO ball
R951WX003	Rp 1/2" x Rp 1/2"	Nickel plated brass	T-handle	Green	DADO ball
R951WX004	Rp 3/4" x Rp 3/4"	Nickel plated brass	T-handle	Green	DADO ball
R951WX005	Rp 1" x Rp 1"	Nickel plated brass	T-handle	Green	DADO ball
R951WX006	Rp 1-1/4" x Rp 1-1/4"	Nickel plated brass	T-handle	Green	DADO ball

Technical data

Main features and materials


- Specific for domestic water
- Full port
- Valve made of UNI EN 12165 CW617N nickel plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium T-handle, green painted
- Heavy series
- DADO ball

Field of applications

- Temperature range: 5÷120 °C
- Max. working pressure at 20 °C with water and not dangerous gas:
4,2 MPa (42 bar) for 3/8", 1/2", 3/4"
3,5 MPa (35 bar) for 1", 1-1/4"

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R951WX002	10	49	25	47	13	63	wr.21	7,0
R951WX003	15	60	30	53	16	63	wr.26	13,3
R951WX004	20	68	34	69	21	77	wr.32	25,8
R951WX005	25	81	41	77	25	77	wr.41	50,9
R951WX006	32	95	48	87	30	77	wr.50	103



Product specifications

R951W

DADO ball valve, with female-female threaded connections. Heavy series. Specific for domestic water. Valve made of UNI EN 12165 CW617N nickel plated brass. Full port. Aluminium T-handle, green painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: 5÷120 °C. Max. working pressure at 20 °C with water and not dangerous gas: 4,2 MPa (42 bar) for 3/8", 1/2", 3/4"; 3,5 MPa (35 bar) for 1", 1-1/4".

Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📠 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com

This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.

The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy