

BALL VALVES

0818EN January 2018

VALVE FOR WATER FOR HEATING/COOLING SYSTEMS
AND NOT DANGEROUS GAS
FULL PORT - R851T SERIES



R851T

Description

Ball valve, with female-female threaded connections, with probe holder M10x1 mm female threaded, for probe \varnothing 6 mm.
Full port.

Versions and product codes

Product code	Connections	Finishing	Handle type	Handle color	Notes
R851TY103	1/2"F (ISO 228) x 1/2"F (ISO 228)	Brass	T-handle	Red	With probe holder
R851TY104	3/4"F (ISO 228) x 3/4"F (ISO 228)	Brass	T-handle	Red	With probe holder
R851TY105	1"F (ISO 228) x 1"F (ISO 228)	Brass	T-handle	Red	With probe holder

Technical data

Main features and materials


- Suitable for water for heating/cooling systems and not dangerous gas
- Full port
- Valve made of UNI EN 12165 CW617N brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Aluminium T-handle, red painted
- Probe holder M10x1 mm female threaded, for probe \varnothing 6 mm.

Field of applications

- Temperature range: $-20 \div 120$ °C (-20 °C with 50 % glycol solutions)
- Max. working pressure at 20 °C with water and not dangerous gas:
3,5 MPa (35 bar) for 1/2" - 3/4"
2,8 MPa (28 bar) for 1"

Dimensions and Kv

Product code	DN	A [mm]	I [mm]	B [mm]	J [mm]	C [mm]	H [mm]	Kv
R851TY103	15	53	27	73	35	63	25	12,7
R851TY104	20	60	30	80	37	73	31	24,6
R851TY105	25	74	37	86	39	73	38	48,5



Product specifications

R851T

Ball valve, with female-female threaded connections. Suitable for water for heating/cooling systems and not dangerous gas. Valve made of UNI EN 12165 CW617N brass. Full port. Aluminium T-handle, red painted. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Probe holder M10x1 mm female threaded, for probe \varnothing 6 mm. Temperature range: $-20 \div 120$ °C (-20 °C with 50 % glycol solutions). Max. working pressure at 20 °C with water and not dangerous gas: 3,5 MPa (35 bar) for 1/2" - 3/4"; 2,8 MPa (28 bar) for 1".

BALL VALVES

0818EN January 2018

VALVE FOR WATER FOR HEATING/COOLING SYSTEMS
AND NOT DANGEROUS GAS
FULL PORT - R851T SERIES



GIACOMINI
WATER E-MOTION



Additional information

For more information, go to www.giacomini.com or contact our technical assistance service: ☎ +39 0322 923372 📞 +39 0322 923255 ✉ consulenza.prodotti@giacomini.com
This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith.
The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.
Giacomini S.p.A. Via per Alzo, 39 - 28017 San Maurizio d'Opaglio (NO) Italy